AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Currently Amended) A connector for connecting circuit boards with each other, comprising:

a first connector section disposed on a first circuit board and having contact terminals electrically connected to an electro-conductive layer of said first circuit board, and

a second connector section disposed on a second circuit board provided in relation to said first circuit board and having contact terminals electrically connected to an electro-conductive layer of said second circuit board with said contact terminals of said second connector being connected electrically to said contact terminals of said first connector section.

wherein when said first connector section is coupled to said second connector section, non-elastic metallic engaging portions provided in said first connector section are engaged latched with elastic metallic portions provided projections provided on an inner surface of an elastic piece in said second connector section to hold said first connector section on said second connector section.

- 2. (Canceled).
- 3. (Previously Presented) A connector as claimed in claim 9, wherein said metallic holding fixture is formed in a thin sheet-like form separately from a base for supporting said contact terminals in said first or said second connector section.

Customer No. 22,852 Application No. 10/619,489 Attorney Docket No. 04208.0183-00000

- 4. (Previously Presented) A connector as claimed in claim 9, wherein said metallic holding fixture has legs fixed to said first or said second circuit board.
 - 5. (Canceled).
 - 6. (Canceled).
- 7. (Previously Presented) A connector as claimed in claim 1, wherein said engaging portions of said first connector section are embedded in one piece and fixed in a base of said first connector section.
- 8. (Previously Presented) A connector as claimed in claim 9, wherein said engaging portions of said first connector section are embedded in one piece and fixed in a base of said first connector section.
- 9. (Currently Amended) A connector for connecting circuit boards with each other, comprising:

a first connector section disposed on a first circuit board and having contact terminals electrically connected to an electro-conductive layer of said first circuit board, and

a second connector section disposed on a second circuit board provided in relation to said first circuit board and having contact terminals electrically connected to an electro-conductive layer of said second circuit board with said contact terminals of said second connector being connected electrically to said contact terminals of said first connector section.

wherein when said first connector section is coupled to said second connector section, non-elastic metallic engaging portions provided in said first connector section are engaged latched with elastic metallic portions projections provided on an inner surface of an elastic piece provided in said second connector section to hold said first connector section on said second connector section and said engaging portions in said first connector section and said engaging portions in said second connector section are nibs and projections of a metallic holding fixture, respectively.

10. (Currently Amended) A connector for connecting circuit boards with each other, comprising:

a first connector section disposed on a first circuit board and having contact terminals electrically connected to an electro-conductive layer of said first circuit board, and

a second connector section disposed on a second circuit board provided in relation to said first circuit board and having contact terminals electrically connected to an electro-conductive layer of said second circuit board with said contact terminals of said second connector being connected electrically to said contact terminals of said first connector section,

wherein when said first connector section is coupled to said second connector section, non-elastic metallic engaging portions provided in said first connector section are engaged latched with elastic metallic portions projections provided on an inner surface of an elastic piece provided in said second connector section to hold said first connector section on said second connector section and a recess is formed for allowing

Customer No. 22,852 Application No. 10/619,489 Attorney Docket No. 04208.0183-00000

a portion being engaged in said second connector section to advance/retract at a base of said second connector section.

11. (Currently Amended) A connector for connecting circuit boards with each other, comprising:

a first connector section disposed on a first circuit board and having contact terminals electrically connected to an electro-conductive layer of said first circuit board, and

a second connector section disposed on a second circuit board provided in relation to said first circuit board and having contact terminals electrically connected to an electro-conductive layer of said second connector circuit board with said contact terminals of said second connector being connected electrically to said contact terminals of said first connector section,

wherein when said first connector section is coupled to said second connector section,[[,]] nibs of a non-elastic metallic holding fixture provided in said first connector section are engaged latched with projections provided on an inner surface of an elastic metallic holding fixture provided in said second connector section to hold said first connector section on said second connector section, said first connector section having leg portions fixed to said first circuit board and said second connector section having leg portions fixed to said second circuit board.

12. (Previously Presented) A connector as claimed in claim 9, wherein a recess is formed for allowing a portion being engaged in said second connector section to advance/retract at a base of said second connector section.

Customer No. 22,852 Application No. 10/619,489 Attorney Docket No. 04208.0183-00000

13. (Previously Presented) A connector as claimed in claim 11, wherein a recess is formed for allowing a portion being engaged in said second connector section to advance/retract at a base of said second connector section.